



Brilliance in Confidence Monitoring



Model 22080 Two Pack Video Monitor

Dual Enhanced 8.4 Inch LCD Screens

The Strength of Brilliant Two Pack Monitoring

- Processes extensive computer input formats
- Exceptionally high brightness and contrast ratio
- Perfect side-to-side and top-to-bottom viewing
- Front panel on screen controls
- Receives S Video and NTSC/PAL (autoswitchable)
- 5+ years LCD field replaceable backlight
- Adjustable vertical tilt
- Superior energy savings

Two Pack Applications

- **Master Control Rooms & Monitor Walls**
- **Post Production and Edit Bays**
- **Cable Head-in & Video Transmission**
- **Mobile/ENG**
- **Teleconferencing**
- **Production and Graphics Design**
- **Surveillance and Security**
- **Satellite and Telco Feeds**

Prominent Users of Data Check Monitors Include:

ABC News At The White House
AOL Time Warner
Armed Forces Radio & TV Services
Avaya
Canadian Broadcast Network
CBS Television City
Cisco Systems
Disney

ESPN
G.E. Americom
Industrial Light + Magic
KOMO-TV
Lucent Technologies
NASA
Pan Am Satellite
Pan American Sports Network

PBS
Sea Launch
Televisa
The White House
Turner Broadcasting
U.S. Navy
Viacom
WBNS-TV



Model 22080 Two Pack Monitor

Model 22080 Technical Specifications

General Description:

Two 4x3 aspect ratio LCD color displays tilting +/-20 degrees
Displays 4x3 and 16x9

Dimensions/Weight:

H 6.97" (4 RU), W 19", D 5"
7 lbs (15 Kg)

Power:

Internal power supply 115/230 VAC
25 watts consumption

Interface:

Composite video input with loop through output, NTSC/PAL autoswitchable,
and S-Video
Computer inputs (ARGB)-15 pin sub D, VGA, SVGA, XGA, SXGA,
75 ohm/Hi Z impedance switch

Controls:

Brightness, contrast, color, position, tint
OSD, front panel control
Three color LED tally lights, self-powered

LCD/TFT Display:

Luminance-400 cd/m²
Contrast ratio-500:1
Native Resolution- Horizontal 640; Vertical 480 (color pixels)
Viewing angle(CR>10:1)-130 degrees horizontal, 110 degrees vertical
Pixel pitch (mm)-0.267 (H) x 0.267 (V)
Response time (ms)-10Tr, 25Tf)
Display area-6.73"W x 5.05" H
Display surface-antireflective film coating
Backlight life-50,000 hours
Backlight components-2 tubes CCFL, field replaceable