



## Model #: RS-1215

### Tripp Lite Power Strip - Multiple outlets wherever you need them

#### Highlights

- Designed for standard 19-inch racks (1U high)
- 12 outlets (6 front / 6 rear)
- 15-amp circuit breaker
- 15 ft. cord



#### Description

Tripp Lite's RS-1215 Power Strip offers 15 amp capacity AC power distribution in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under-counter installation. Uses only 1 rack space (1U) when installed in any 19 inch rack meeting EIA standards. Unfiltered electrical pass-through makes RS-1215 ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 12 NEMA5-15R outlets (6 front/6 rear), 15 ft AC power cord and lighted switch with cover prevents risk of accidental turn-off.

PLUG/OUTLETS: Input: NEMA 5-15P

Output: 12 NEMA5-15R (6 front & 6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: Supports 19 in. rackmount (uses 1 rack space/1U), wallmount, under-counter and more

#### Applications

- Offers multiple outlet power distribution for multiple loads in 19 inch rackmount, wallmount and under-counter applications, such as internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS, generator or commercially derived AC power to protected equipment.

#### Package Includes

- RS-1215
- Mounting hardware
- Instruction manual

#### Features

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- Uses one rack space (1U) in standard 19 inch rack ("zero U" mounting possible in many racks)
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 12 NEMA5-15R output receptacles (6 front/6 rear)
- 15 foot AC cord NEMA5-15P plug connection

- Lighted power switch confirms power on/off status
- Snap-in switch guard prevents accidental turn off
- 15 amp electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

## Specifications

| <b>SYSTEM OVERVIEW</b>                               |  |
|--|--|
| Voltage compatibility                                | 120VAC   |
| <b>OUTPUT</b>  |  |
| Frequency compatibility                              | 50 / 60 Hz   |
| Output volt amp capacity (amps)                      | 15   |
| Outlet quantity / type                               | 12 NEMA 5-15R  |
| Outlet orientation                                   | 6 front facing / 6 rear facing                                   |
| <b>INPUT</b>   |  |
| Recommended Electrical Service                       | 15A 120V   |
| Input connection type                                | NEMA 5-15P   |
| Input cord length (ft.)                              | 15   |
| Input cord length (m)                                | 4.572  |
| <b>LEDS ALARMS &amp; SWITCHES</b>                    |  |
| Switches   | Red illuminated 2 positon switch controls power to all outlets   |
| Locking switch cover                                 | Transparent locking switch cover prevents accidental shutoff     |
| <b>PHYSICAL</b>                                      |  |
| Unit Dimensions (HWD/in)                             | 1.75 (1U) x 17.5 x 4.5   |
| Unit Dimensions (HWD/cm)                             | 4.445 x 44.45 x 11.4   |
| Material of construction                             | Sheet metal  |
| Receptacle Color                                     | Black  |
| AC line cord color                                   | Black  |
| Form factors supported                               | 1U rackmount, wall-mount and undercounter installation supported |
| <b>SPECIAL FEATURES</b>                              |  |
| TVSS grounding                                       | Back panel nut and bolt grounding lug                            |
| <b>CERTIFICATIONS</b>                                |  |
| UL1363 (Power Tap)                                   | UL1363 (UR status)   |
| cUL / CSA (Canada)                                   | cUL  |
| <b>WARRANTY</b>                                      |  |
| Product Warranty Period (U.S., Canada & Puerto Rico) | Lifetime   |