

CCH SPEC ADAPTER PANELS

These come available with any industry standard connector type, and fiber counts ranging from 6 to 24 simplex fiber ports per panel. Panels are a durable powder coated black steel, with ports numerically labeled in white print. LC and SC connector types are available in non-keyed color coded in addition to the TIA standard colors.

All adapters are compliant with TIA/EIA 568-B.3 and TIA/EIA-455-21A.



ORDERING INFORMATION

GFAPC-(AAA)(B)-(DD)-(EE)*

AAA = SELECT FIBER COUNT

006 - 144

DD = SELECT CONNECTOR TYPE

LC	LC DUPLEX
LA	LC/APC DUPLEX
JN	MTRJ
MF	MPO
SC	SC DUPLEX
SA	SC/APC DUPLEX

B = SELECT FIBER TYPE

Y	OS2
F	OM1
E	OM2
G	OM3/4
P	OM5

EE (OPTIONAL) = SELECT COLOR

BL	BLUE
OR	ORANGE
GR	GREEN
BR	BROWN
SL	SLATE
WH	WHITE
RD	RED
BK	BLACK
YL	YELLOW
VL	VIOLET
PK	ROSE
AQ	AQUA

EXAMPLE PART NUMBER:

GFAPC-12Y-LC

EXAMPLE DESCRIPTION:

CCH Spec Adapter Panel, 12F, OS2, duplex blue LC-UPC

*(EE) is optional ordering information for non-keyed colored adapters, available only in SC and LC